


LISTEN.
THINK.
SOLVE.®

Product Data Sheet

Power Distribution Terminal Blocks
Catalog Number: 1492-50XF



Ratings:

175 Amps
600 Volts AC/DC
Panel Mount

Wire Range:

Line Side: (1) 2/0 - #14 AWG
Load Side: (1) ¼ - 20 Tapped Hole

Agency Approvals:

- UL Recognized, UL 1059 Terminal Block Standard – File #XCFR2.E40735
- CSA Certified, CSA C22.2 No. 158 (Wire Class B & C only)
- CE Compliant to IEC 60947-7-1
- RoHS Compliant

Electrical Ratings:

- 175 Amp Copper Wire (Based on NEC Table 310-16, 75°C Column)
- 600 Volts AC/DC (UL 1059 Class C, User Group – General Industrial)
- Factory and Field Wiring

Mechanical Ratings:

Mounting Information:

- Panel Mount: #10 Fastener, Torque to 25-30 in-lbs
- Terminal Keys Needed: 5/16"

Thermal Information*:

- Storage Temperature range:
 - -35°C to 110°C (-31°F to 230°F)

- Max. Insulator base temperature: 150°C (302°F) UL RTI
- Flammability rating of insulator base and base plate: UL 94 V-0

* Use outside these ratings needs to be judged in the end-use application.

Materials:

- Connector: High Conductivity Aluminum, Tin-Plated
- Insulator Base: Phenolic
- Terminal Set Screws: Aluminum, Tin-Plated
- Connector Mounting Screw: Steel, Zinc-Plated

Accessories:

- Clear Protective Plastic Cover. Catalog Number: 1492-PBC1
- Marking Strip: White vinyl strip to mark circuits (Supplied with block)



Product Data Sheet

Power Distribution Terminal Blocks
Catalog Number: 1492-50XF

Short Circuit Current Ratings (Copper Wire Only): Default Rating 10kA.

Wire Approvals:

Line Side Wire Approvals:

- Wire Strip Length, Line Side Tap – 3/4"




Wire Size (AWG)	Torque (In-lbs)	UL Copper Wire Stranding Classes - Number of Strands						
		Solid	Class B	Class C	Class G	Class H	Class I	Class K
2/0	120		19	37				
1/0	120		19	37				
1	120		19	37	133*	259*	210*	836*
2	120		7	19	49*	133*	161*	665*
4	120		7	19	49*	133*	105*	420*
6	120		7	19	49*	133*	63*	266*
8	40		7	19	49*	133*	41*	168*
10	35	1	7	19			27*	104*
12	35	1	7	19			19*	65*
14	35	1	7	19			19*	41*

* Quantity of wire stands for classes G, H, I, K may vary by manufacturer

Load Side Wire Approvals:

- Wire Strip Length, Load Side Tap – 3/4"
- 1/4 - 20 Tapped Hole





Product Data Sheet

Power Distribution Terminal Blocks
Catalog Number: 1492-50XF

Product Dimensions / Drawings:

	<p>1492-50XF POWER BLOCK, TAP WITH BINDING SCREW BLOCK, 3 POLE 1 LINE-1 LOAD, 115 AMPS</p>