

LISTEN.
THINK.
SOLVE.®

Product Data Sheet

Power Distribution Terminal Blocks
Catalog Number: 1492-PDL3163



Ratings:

335 Amps
600 Volts AC/DC
Panel Mount

Wire Range:

Line Side: (1) 400kcmil - #6 AWG
Load Side: (6) #2 - #14 AWG

Agency Approvals:

- UL Recognized, UL 1059 Terminal Block Standard – File #XCFR2.E40735
- UL 508A Feeder Circuit Terminal Spacing for up to 600VAC.
- CSA Certified, CSA C22.2 No. 158
- 600VAC Rating for Class 6228 01 – Use Groups A, B, C
- CE Compliant to IEC 60947-7-1
- RoHS Compliant

Electrical Ratings:

- 335 Amp Copper Wire (Based on NEC Table 310-16, 75°C Column)
- 600 Volts AC/DC (UL 1059 Class C, User Group – General Industrial)
- Factory and Field Wiring

Mechanical Ratings:

Mounting Information:

- Panel Mount: #10 Fastener,
 - Torque to 25-30 in-lbs
- Terminal Keys Needed:
 - Line Side: 5/16", Load Side: 5/32"

Thermal Information*:

- Storage Temperature range:
 - -35°C to 125°C (-31°F to 257°F)

- Max. Insulator base temperature: 125°C (257°F) UL RTI
- Max. Insulator base plate temperature: 130°C (266°F) UL RTI
- Flammability rating of insulator base and base plate: UL 94 V-0

* Use outside these ratings needs to be judged in the end-use application.

Materials:

- Connector: High Conductive Aluminum, Tin-Plated
- Insulator Base: Glass Filled Polycarbonate (Thermoplastic)
- Terminal Set Screws: Aluminum, Tin-Plated and Steel, Nickel-Plated
- Connector Mounting Screw: Steel, Zinc-Plated
- Insulator Base Plate: Phenolic Laminate

Accessories:

- Protective Hinged Plastic Cover (Supplied with Product)
- Marking Strip: White vinyl strip to mark circuits (Supplied with Product)



Product Data Sheet

Power Distribution Terminal Blocks
 Catalog Number: 1492-PDL3163

Short Circuit Current Ratings (Copper Wire Only): Default Rating 10kA if not listed in Table:

Wire Range (kcmil/AWG)		Max Fuse Protection Requirements Amp Rating / Class						SCCR RMS Amps (600V Max)
Line	Load	J	T	RK1	RK5	G	CC	
400 – 3/0	2 – 8	400	400	400	100	60	30	100,000
2/0 – 6	2 – 14	200	200	200	100	60	30	100,000

Wire Range (AWG)		Circuit Breaker Overcurrent Protection Requirements			SCCR RMS Amps (480V Max)
Line	Load	Mfr	Cat #	Max Amp	
400 – 3	2 – 3	Allen Bradley	140U-K6	400	35,000
350 – 4	2 – 8		140U-J6	250	50,000
			140U-J0	250	50,000

Wire Approvals:

Line Side Wire Approvals:

- Wire Strip Length, Line Side Tap – 1-3/16”




Wire Size (kcmil/AWG)	Torque (In-lbs)	UL Copper Wire Stranding Classes - Number of Strands		
		Solid	Class B	Class C
400	275		37	61
350	275		37	61
300	275		37	61
250	275		37	61
4/0	275		19	37
3/0	275		19	37
2/0	275		19	37
1/0	275		19	37
1	275		19	37
2	275		7	19
4	275		7	19
6	275		7	19



Product Data Sheet

Power Distribution Terminal Blocks
Catalog Number: 1492-PDL3163



Load Side Wire Approvals:

- Wire Strip Length, Load Side Tap – Top Row: 9/16", Bottom Row: 1-1/16"

Wire Size (kcmil/AWG)	Torque (In-lbs)	UL Copper Wire Stranding Classes - Number of Strands		
		Solid	Class B	Class C
2	50		7	19
4	45		7	19
6	45		7	19
8	40		(1-2)* 7	(1-2)* 19
10	35	1	(1-2)* 7	(1-2)* 19
12	35	1	(1-4)* 7	(1-4)* 19
14	35	1	(1-4)* 7	(1-4)* 19

**When using multiple wire connections, SCCR rating is reduced to default rating of 10kA*



Product Data Sheet

Power Distribution Terminal Blocks
Catalog Number: 1492-PDL3163

Product Dimensions / Drawings:

