










BULLETIN 1492 SPRING-CLAMP TERMINAL BLOCKS

1 & 2 CIRCUIT FEED-THROUGH PLUG-IN CONNECTION BLOCKS

	1492-L31P	1492-L3T1P	1492-L3Q2P			
Dimensions are not intended to be used for manufacturing purposes.						
Note: Height dimension is measured from top of rail to top of terminal block.						
Specifications	Single-circuit terminal block with 1 fixed and 1 plug-in connection. Plug-in connectors can be individual or grouped configurations.	Single-circuit terminal block with 2 fixed and 1 plug-in connection. Plug-in connectors can be individual or grouped configurations.	Single-circuit terminal block with 2 fixed and 2 plug-in connection. Plug-in connectors can be individual or grouped configurations.			
Certifications	 CSA 	 CSA 	 CSA 			
Voltage Rating	300V AC/DC	300V AC/DC	300V AC/DC			
Maximum Current	20 A	20 A	20 A			
Limited Rating - Voltage *	600V AC/DC	600V AC/DC	600V AC/DC			
Limited Rating - Current *	5 A	5 A	5 A			
Wire Range (Rated Cross Section)	26... 12 AWG	26... 12 AWG	26... 12 AWG			
Wire Strip Length	0.394 in (10 mm)	0.394 in (10 mm)	0.394 in (10 mm)			
Density (Blocks per foot/meter)	59 per ft/196 per meter	59 per ft/196 per meter	59 per ft/196 per meter			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)	-58...+248 °F (-50...+120 °C)	-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.	Pcs/Pkg	Cat. No.	Pcs/Pkg	Cat. No.	Pcs/Pkg
Color Gray	1492-L31P	50	1492-L3T1P	50	1492-L3Q2P	50
Accessories	Cat. No.	Pcs/Pkg	Cat. No.	Pcs/Pkg	Cat. No.	Pcs/Pkg
Mounting Rails						
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2
End Barrier Gray	1492-EBL31P	50	1492-EBL3T1P	50	1492-EBL3Q2P	50
Yellow	1492-EBL31P-Y	50	1492-EBL3T1P-Y	50	—	—
End Anchors						
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20
DIN Rail - Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100
Din Rail - Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50
Jumpers						
Plug-in Center Jumper — 50 Pole	1492-CJLJ5-50	10	1492-CJLJ5-50	10	1492-CJLJ5-50	10
Plug-in Center Jumper — 10 Pole	1492-CJLJ5-10	20	1492-CJLJ5-10	20	1492-CJLJ5-10	20
Plug-in Center Jumper — 9 Pole	1492-CJLJ5-9	20	1492-CJLJ5-9	20	1492-CJLJ5-9	20
Plug-in Center Jumper — 8 Pole	1492-CJLJ5-8	20	1492-CJLJ5-8	20	1492-CJLJ5-8	20
Plug-in Center Jumper — 7 Pole	1492-CJLJ5-7	20	1492-CJLJ5-7	20	1492-CJLJ5-7	20
Plug-in Center Jumper — 6 Pole	1492-CJLJ5-6	20	1492-CJLJ5-6	20	1492-CJLJ5-6	20
Plug-in Center Jumper — 5 Pole	1492-CJLJ5-5	20	1492-CJLJ5-5	20	1492-CJLJ5-5	20
Plug-in Center Jumper — 4 Pole	1492-CJLJ5-4	60	1492-CJLJ5-4	60	1492-CJLJ5-4	60
Plug-in Center Jumper — 3 Pole	1492-CJLJ5-3	60	1492-CJLJ5-3	60	1492-CJLJ5-3	60
Plug-in Center Jumper — 2 Pole	1492-CJLJ5-2	60	1492-CJLJ5-2	60	1492-CJLJ5-2	60
Other Accessories						
Test Adapter	1492-TPL5P	25	1492-TPL5P	25	1492-TPL5P	25
Individual Plug-in Connector Gray	1492-STP	50	1492-STP	50	1492-STP	50
Green	1492-STP-G	50	1492-STP-G	50	1492-STP-G	50
Ganged Connector - Start Plug Gray	1492-SBSTP	50	1492-SBSTP	50	1492-SBSTP	50
Ganged Connector - Middle Plug ‡ Gray	1492-GSTP	50	1492-GSTP	50	1492-GSTP	50
Ganged Connector - End Plug Gray	1492-EBSTP	50	1492-EBSTP	50	1492-EBSTP	50
Plug-In Component Accessories						
Locking Element Yellow	1492-STPLE	25	1492-STPLE	25	1492-STPLE	25
Coding Element Yellow	1492-STPCE	50	1492-STPCE	50	1492-STPCE	50
Strain Relief Yellow	1492-STPSR	25	1492-STPSR	25	1492-STPSR	25
Group Marking						
Rail Mount Group Marking Carrier	1492-GM35	25	1492-GM35	25	1492-GM35	25
End Anchor Top Marker Carrier *	1492-GMC	50	1492-GMC	50	1492-GMC	50
Cat. No. 1492-GMC Top Marker Tag	1492-M5X30(20/card)	5	1492-M5X30(20/card)	5	1492-M5X30(20/card)	5
Marking Systems						
Snap-in Marker Cards	1492-MR5X12 (120/card)	5	1492-MR5X12 (120/card)	5	1492-MR5X12 (120/card)	5
Snap-In Marker Cards	1492-MR5X8 (120/card)	5	1492-MR5X8 (120/card)	5	1492-MR5X8 (120/card)	5

* The Bulletin 1492-GMC marker carrier installs directly on the top of a 1492-EAJ35 end anchor or a 1492-ERL35 end retainer for group marking purposes.

‡ Blocks contain dual UL/CSA listings and can be used at 300V with a 20 A rating or 600V with a 5 A rating.

‡ For ganged configurations greater than 2, use multiple 1492-GSTP plug-in blocks.