

# Spring-Clamp Connection Terminal Blocks

## 2-Level Neutral Disconnect and Installations

	1492-LDG3ND			1492-LD3N			1492-LDG3N		
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.									
<b>Specifications</b>	3-Level terminal block with neutral disconnect and ground connection			2-Level feed-through terminal block for installation applications			3-Level terminal block with 2 feed-through and ground connection		
<b>Certifications</b>		<b>CSA</b>	<b>IEC</b>		<b>CSA</b>	<b>IEC</b>		<b>CSA</b>	<b>IEC</b>
<b>Voltage Rating</b>	600V AC/DC	300V AC/DC	400V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC
<b>Maximum Current</b>	15 A	10 A	24 A	15 A	10 A	24 A	15 A	10 A	24 A
<b>Wire Range (Rated Cross Section)</b>	#26...12 AWG		2.5 mm <sup>2</sup>	#26...12 AWG		2.5 mm <sup>2</sup>	#26...12 AWG		2.5 mm <sup>2</sup>
<b>Wire Strip Length</b>	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
<b>Density</b>	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
<b>Short-Circuit Current Rating</b>	See page 12-78								
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>
Color: Grey	1492-LDG3ND	50	1492-LD3N	50	1492-LDG3N	50	1492-LDG3N	50	1492-LDG3N
<b>Accessories</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>	<b>Pkg Qty.</b>	<b>Cat. No.</b>
<b>Mounting Rails:</b>									
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10	<b>199-DR1</b>	10	<b>199-DR1</b>	10	<b>199-DR1</b>	10	<b>199-DR1</b>
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	<b>1492-DR5</b>
1 m Hi-Rise Sym. DIN (Aluminum)	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	<b>1492-DR6</b>
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	<b>1492-DR7</b>
End Barriers/ Busbar Support Plates Grey	<b>1492-BSPJLD3N</b>	20	<b>1492-BSPJLD3N</b>	20	<b>1492-BSPJLD3N</b>	20	<b>1492-BSPJLD3N</b>	20	<b>1492-BSPJLD3N</b>
Blue	<b>1492-BSPJLD3N-B</b>	20	<b>1492-BSPJLD3N-B</b>	20	<b>1492-BSPJLD3N-B</b>	20	<b>1492-BSPJLD3N-B</b>	20	<b>1492-BSPJLD3N-B</b>
<b>End Anchors and Retainers:</b>									
Screwless End Retainer	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>
End Anchor — Normal Duty	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>
End Anchor — Heavy Duty	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>
Plug-in Center Jumper — 10-Pole	<b>1492-CJLJ5-10</b>	20	<b>1492-CJLJ5-10</b>	20	<b>1492-CJLJ5-10</b>	20	<b>1492-CJLJ5-10</b>	20	<b>1492-CJLJ5-10</b>
Plug-in Center Jumper — 4-Pole	<b>1492-CJLJ5-4</b>	60	<b>1492-CJLJ5-4</b>	60	<b>1492-CJLJ5-4</b>	60	<b>1492-CJLJ5-4</b>	60	<b>1492-CJLJ5-4</b>
Plug-in Center Jumper — 3-Pole	<b>1492-CJLJ5-3</b>	60	<b>1492-CJLJ5-3</b>	60	<b>1492-CJLJ5-3</b>	60	<b>1492-CJLJ5-3</b>	60	<b>1492-CJLJ5-3</b>
Plug-in Center Jumper — 2-Pole	<b>1492-CJLJ5-2</b>	60	<b>1492-CJLJ5-2</b>	60	<b>1492-CJLJ5-2</b>	60	<b>1492-CJLJ5-2</b>	60	<b>1492-CJLJ5-2</b>
<b>Other Accessories:</b>									
Partition Plate									
Neutral Connection Block (4 mm) Blue	*	1492-JNC4-B	50	—	—	—	—	—	—
Neutral Connection Bloc (16 mm) Blue	*	1492-JNC16-B	50	—	—	—	—	—	—
Neutral Bus Bar (1 m)		1492-NBB3-1M	5	—	—	—	—	—	—
<b>Marking Systems:</b>									
Snap-in Marker Cards	<b>1492-M5X5</b>	(200/card)	5	<b>1492-M5X5</b>	(200/card)	5	<b>1492-M5X5</b>	(200/card)	5

\* These terminals mount on Cat. No. 1492-NBB3-1M Neutral Busbar. They can accept Cat. No. 1492-M6X5 snap-in markers.