















## Spring-Clamp Connection Terminal Blocks

## Grounding Blocks, Continued

	1492-LG16				1492-LG35				1492-LDG2			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
<b>Specifications</b>	Feed-through Ground Block				Feed-through Ground Block				Two-Circuit Block with 1 Feed-Through and 1 Ground Circuit			
<b>Certifications</b>												
<b>Voltage Rating</b>	—				—				300V AC/DC		500V AC/DC	
<b>Maximum Current</b>	Grounding				Grounding				10 A		17.5 A	
<b>Wire Range (Rated Cross Section)</b>	#14...6 AWG	#14...4 AWG	16 mm <sup>2</sup>	16 mm <sup>2</sup> (16...6 AWG)	#12...2 AWG	35 mm <sup>2</sup>	35 mm <sup>2</sup> (#14...2 AWG)		#28...16 AWG	1.5 mm <sup>2</sup>		
<b>Wire Strip Length</b>	0.70 in. (18 mm)				0.98 in. (25 mm)				0.31 in. (8 mm)			
<b>Density</b>	25 pcs/ft (82 pcs/m)				18 pcs/ft (62 pcs/m)				87 pcs/ft (285 pcs/m)			
<b>Housing Temperature Range</b>	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
<b>Terminal Blocks</b>	<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>	
<b>Color:</b>	Green/Yellow		1492-LG16		25		1492-LG35		10		—	
	Grey		—		—		—		1492-LDG2		50	
<b>Accessories</b>	<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>		<b>Cat. No.</b>		<b>Pkg Qty.</b>	
<b>Mounting Rails:</b>	1 m Symmetrical DIN (Steel)		199-DR1		10		199-DR1		10		199-DR1	10
	1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)		199-DR4		5		199-DR4		5		199-DR4	5
	1 m Symmetrical DIN (Aluminum)		1492-DR5		10		1492-DR5		10		1492-DR5	10
	1 m Hi-Rise Symmetrical DIN (Aluminum)		1492-DR6		2		1492-DR6		2		1492-DR6	2
	1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2		1492-DR7		2		1492-DR7	2
	1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)		1492-DR8		5		1492-DR8		5		1492-DR8	5
	1 m Symmetrical Heavy Duty DIN (Steel)		1492-DR9		5		1492-DR9		5		1492-DR9	5
<b>End Barrier</b>	Yellow		1492-EBL16-Y		20		Integrated		—		—	
	Grey		—		—		—		1492-EBLD2		50	
<b>End Anchors and Retainers</b>	Screwless End Retainer		1492-ERL35		20		1492-ERL35		20		1492-ERL35	20
	DIN Rail — Normal Duty		1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35	100
	DIN Rail — Heavy Duty		1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35	50
<b>Other Accessories:</b>	Reducing Sleeves 26...24 AWG (0.13...0.2 mm <sup>2</sup> ) White		—		—		—		1492-PSL2-2		100	
	Reducing Sleeves 22...20 AWG (0.25...0.5 mm <sup>2</sup> ) Grey		—		—		—		1492-PSL2-5		100	
	Test Plug		1492-TP23		20		1492-TP23		20		1492-TPL4	25
	Electrical Warning Plate		—		—		—		1492-EWPL4		20	
	Group Marking Carrier		1492-GM35		25		1492-GM35		25		1492-GM35	25
<b>Marking Systems:</b>	Snap-In Marker Cards*		1492-M7X12 (108/card)		5		1492-M7X12 (108/card)		5		1492-M3X12 (120/card)	5
	Snap-In Marker Cards		1492-M8X5 (160/card)		5		1492-M8X5 (160/card)		5		1492-M3X5 (100/card)	5
	Hinged Marker Cards		1492-MH5X15 (96/card)		5		1492-MH5X10 (96/card)		—		—	—

\* May only be mounted in terminal block corner marking positions.