

SPECIFICATIONS:

1. MOTOR INFORMATION
   - MOTOR TYPE: VARIABLE SPEED AC
   - FRAME SIZE: RDL1613Y
   - RATING: 73.7 KW
   - VOLTAGE: 400
   - ENCLOSURE: TOTALLY ENCLOSED IP54
   - MOUNTING: FLANGE (350mm BOLT CIRCLE)
   - COOLING: BLOWER COOLED IC416
   - DRIVE METHOD: COUPLED OR BELTED
   - ACCESSORIES: ENCODER & BRAKE
2. CONTINUOUS STALL TORQUE: 237 Nm MAX AT 155°C WINDING TEMPERATURE, IN A 40°C AMBIENT
3. OPERATING SPEED: 3000 BASE SPEED / 5000 RPM MAX.
4. 1024 SINUSOID/REV ENCODER, WITH SINGLE-TURN ABSOLUTE POSTION DATA
5. FOR ADDITIONAL SPECIFICATIONS SEE 10000000343
6. SHAFT HEIGHT WILL NOT BE EXCEEDED SHIMS UP TO 0.5 MM IN THICKNESS USUALLY REQUIRED FOR COUPLED OR GEARED MACHINES.
7. SHAFT EXTENSIONS ARE ACCORDING TO DIN 748, TOLERANCES ARE BASED ON THE ISA FITTING SYSTEM USING k6 FOR DIAMETERS UP TO 50MM AND m6 FOR DIAMETERS ABOVE.
8. MAX SHAFT TIR .06 [.002] MAX FACE TIR .13 [.005]
9. MOTOR WEIGHT 305 KG. [672 LBS] (MAY VARY 15%)
10. BRAKE: 400VAC 20 Nm MAX. HOLDING TORQUE, BRAKE RELEASES WHEN VOLTAGE APPLIED

BLOWER CONNECTION	
SERIES	
LEAD	400 VOLTS
T1	L1
T2	L2
T3	L3
T4	
T5	
T6	
T7	
T8	
T9	

PARALLEL	
LEAD	200 VOLTS
T1	L1
T2	L2
T3	L3
T4	
T5	
T6	
T7	
T8	
T9	

PIN-OUT	
ENCODER CONNECTOR	
PIN	FUNCTION
A	SIN +
B	SIN -
C	COS +
D	COS -
E	DATA +
F	DATA -
G-M	-
N	+9 VDC
P	COM
R	TS +
S	TS -
T-V	-

MOTOR CONNECTION	
TERMINAL BOX	
LEAD	SOURCE
U1	L1
V1	L2
W1	L3
GREEN	GROUND

BRAKE CONNECTION	
460 V 1 PHASE	
LEAD	SOURCE
B1	L1
B2	L2



DRIVE END SHAFT DETAIL SPEC (9)

SUPPLIER PART NUMBER: L16M5280

NOTE: ALL DRAWING MODIFICATIONS REQUIRE CUSTOMER APPROVAL

REFERENCES		DESCRIPTION	CAD DOCUMENT
VERSION/ CHANGE NUMBER	TOLERANCES UNLESS OTHERWISE SPECIFIED DO NOT SCALE DRAWING DIMENSIONS ARE IN MILLIMETERS WITH INCHES REFERENCED [X] UNTOLERANCED DIMENSIONS ARE REFERENCETHIRD ANGLE PROJECTION	HPK-E1613E-SB44AA,ESM	Allen-Bradley Rockwell Automation
		DR. AMB	DATE 09-19-06
		DXF FILE AVAILABLE	SHEET 1 OF 1 DWG. SIZE B DOCUMENT NUMBER 10000000363