


PHASE - NEUTRAL BACK EMF, ENCODER ABSOLUTE POSITION



SIN+, SIN-, COS+, COS- ENCODER OUTPUT WAVEFORMS



SHAFT LOAD RATING for 20,000 hour L10 bearing life and RADIAL LOAD applied mid-way along shaft extension




NOTES:

General Specifications:

| | |
|---|--|
| 1. Motor type: 3 phase, wye winding, permanent magnet rotor, totally enclosed, non-ventilated. | |
| 2. Motor poles: | 8 |
| 3. Operating Speed, max | 4000 RPM |
| 4. Base speed (max speed at peak torque), Ref: | 2400 RPM |
| 5. Operating voltage at base speed: | 440 VAC RMS |
| 6. Continuous stall torque, max, at max winding temperature in a 40C ambient: | 10.2 Nm (90 lb-in) |
| 7. Winding temperature, max, in a 40C ambient: | 140 degrees C |
| 8. Continuous stall current, max: | 10.75 Amps 0 to peak |
| 9. Heatsink size, aluminum, attached to front mounting flange for continuous torque specifications: | 305 x 305 x 12.7mm (12 x 12 x 0.5 inch) |
| 10. Peak stall torque, max: | 27.1 Nm (240 lb-in) |
| 11. Peak stall current, max: | 34.25 Amps 0 to peak |
| 12. Rated Speed (Speed at max continuous power) | 3500 |
| 13. Continuous output rating, max at rated speed: | 2.20 kW (2.95 hp) |
| 14. Continuous torque, max, at rated speed: | 6.0 Nm (53 lb-in) |
| 15. Continuous current, Ref, at rated speed: | 5.8 Amps 0 to peak |
| 16. Operating voltage, Ref (Not for direct connection to AC line): | 480 VAC RMS |
| 17. Insulation class: | 155C (Class F) |
| 18. Housing temperature, max: | 125C (257F) |
| 19. Ke, +/-10%, phase to phase at 25C +/- 5C: | 138 V/kRPM 0 to peak |
| 20. Kt (sine), Ref, at 25C +/- 5C: | 1.14 Nm/Amp (10.10 lb-in/Amp) 0 to peak |
| 21. Winding resistance, +/- 10%, phase to phase at 25C +/- 5C: | 1.957 ohms |
| 22. Winding inductance, Ref, phase to phase: | 18.64 mH |
| 23. Dielectric rating of motor power connections (U,V,W), to ground for 1 second: | 1800 VAC RMS 50/60 Hz |
| 24. Audible noise, Ref, at 1 meter distance: | XX dBA |
| 25. Rotor inertia, +/- 10%: | 0.001223 kg-m ² (0.01082 lb-in-sec ²) |
| 26. Rotor balancing quality grade: | G-6.3 |
| 27. Friction torque, Ref: | 0.15 Nm (1.35 lb-in) |
| 28. Friction torque, Ref, with shaft seal option installed: | 0.15 Nm (1.3 lb-in) |
| 29. Cogging torque, Ref: | 0.060 Nm (0.53 lb-in) peak to peak |
| 30. Thermal resistance, Ref, winding to ambient: | 0.49 degrees C/watt |
| 31. Thermal time constant, Ref, winding to ambient: | 30.5 minutes |
| 32. Product weight, Ref: | 9.6 kg (21.2 lb) |
| 33. Shipping weight, Ref: | 10.85 kg (23.9 lb) |
| 34. Operating ambient temperature: | 0C to 40C (32F to 104F) |

Notes:

- "Ref" denotes untoleranced specifications, provided for reference only.
- Speed, torque and current specifications are for operation with Allen Bradley drives.

| | | | | | |
|---|---|--------------------------------------|---------------|----------------------------|--------------------|
|  | CONFIDENTIAL AND PROPRIETARY INFORMATION | Engineering Specification Electrical | | Sheet 2 of 4 | |
| | THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC. | MPM-B1304E-SJ72AA | | Size | 10000073869 |
| | | Dr. Scott Johnson | Date 08-26-09 | A | Ver 01 |

General Specifications, continued:


- 35. Storage ambient temperature: -30C to 70C (-22F to 158F)
- 36. Relative humidity, non-condensing: 5% to 95%
- 37. Liquid / dust protection: IP66
- 38. Shock, max, 6 msec duration: 20 g peak
- 39. Vibration, max, 30 to 2000 Hz: 2.5 g peak
- 40. Shaft material: Steel, 1144
- 41. Paint, color: Black
- 42. Shaft, key (if provided), front mounting surface, and connector mating surfaces are not painted.

Feedback Specifications:

- 1. SIN, COS waveform output: 1024 sinusoids/rev
- 2. SIN, COS waveform amplitude, ± 10%: 1.0 VAC peak to peak
- 3. SIN -, COS - voltage offset with respect to ECOM ±0.3 VDC: 2.2 to 2.8 VDC
- 4. EPWR 5V (encoder power) input voltage: N/A
- 5. EPWR 5V continuous input current,max, at 5.0 VDC: N/A
- 6. EPWR 5V inrush input current, max, when connected to Kinetix6000 drive: N/A
- 7. EPWR 9V (encoder power) input voltage: 7.0 to 12.0 VDC
- 8. EPWR 9V continuous input current,max, at 9.0 VDC: 80 mADC
- 9. EPWR 9V inrush input current, max, when connected to Kinetix6000 drive: 3.9 ADC
- 10. TS+, TS- thermostat operating voltage, max: 250 Volts
- 11. TS+, TS- thermostat continuous current, max, at 0.6 power factor: 1.6 Amps
- 12. TS+, TS- thermostat continuous current, max, at 1.0 power factor: 2.5 Amps
- 13. DATA+, DATA- signal type, rate, asynchronous: RS 485, 9600 baud
- 14. Communication hierarchy: Encoder is slave, communication is externally initiated.
- 15. Single turn absolute position value range: 0 to 32,767 (15 bit)
- 16. Absolute position data: Binary, value increases with CW shaft rotation viewing motor mounting face.
- 17. Data (byte) format: Start bit, 8 data bits, parity bit, stop bit.
- 18. Memory storage capacity, EEPROM: 128 bytes
- 19. Encoder temperature data: Binary value of encoder temperature in degrees C.

Notes:


- 1. "Ref" denotes untoleranced specifications, provided for reference only.

| | | | | | |
|---|---|--------------------------------------|----------|----------------------------|-------------|
|  | CONFIDENTIAL AND PROPRIETARY INFORMATION | Engineering Specification Electrical | | Sheet 3 of 4 | |
| | THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC. | MPM-B1304E-SJ72AA | | Size | 10000073869 |
| | Dr. Scott Johnson | Date | 08-26-09 | A | Ver 01 |

**MPM-B1304E-Sxx2xx Performance with 2094-BC02-M02,
3 Phase at 480 VAC Drive Input, 40C Motor Ambient**

| SPEED RPM | TORQUE | | |
|--------------|--------|------------|------------|
| | Tcont | Tpeak 480V | Tpeak 400V |
| | Nm | Nm | Nm |
| 0 | 10.4 | 27.1 | 27.1 |
| 1000 | 9.6 | 27.1 | 27.1 |
| 2000 | 8.4 | 27.1 | 27.1 |
| 2150 | 8.2 | 27.1 | 27.1 |
| 2650 | 7.4 | 27.1 | 18.9 |
| 3000 | 6.9 | 22.4 | 13.2 |
| 3300 | 6.36 | 18.3 | 8.25 |
| 3300 | 6.36 | 18.3 | 0 |
| 3800 | 5.35 | 11.5 | #N/A |
| 4000 | 5.1 | 8.8 | #N/A |
| 4000 | 0 | 5.1 | #N/A |
| #N/A | #N/A | #N/A | #N/A |

| SPEED RPM | TORQUE | | |
|--------------|--------|------------|------------|
| | Tcont | Tpeak 480V | Tpeak 400V |
| | lb-in | lb-in | lb-in |
| 0 | 92.0 | 239.9 | 239.9 |
| 1000 | 85.0 | 239.9 | 239.9 |
| 2000 | 74.3 | 239.9 | 239.9 |
| 2150 | 72.6 | 239.9 | 239.9 |
| 2650 | 65.5 | 239.9 | 167.3 |
| 3000 | 61.1 | 198.3 | 116.8 |
| 3300 | 56.3 | 162.0 | 73.0 |
| 3300 | 56.3 | 162.0 | 0.0 |
| 3800 | 47.4 | 101.8 | #N/A |
| 4000 | 45.1 | 77.9 | #N/A |
| 4000 | 0.0 | 45.1 | #N/A |
| 4000 | #N/A | #N/A | #N/A |



Notes:

1. Nm torque values shown are converted from tested lb-in data.