



MOUNTING ACCESSORIES see section 8

Material	Connections		Part no.
	Inlet 1 - 2	Outlet	
steel st. st.	G 3/8 female thread according to DIN 3852	DIN EN 61518 Type A	S345.06.114.11 S345.06.214.11
steel st. st.	tube fitting O. D. 12 mm, line S		S345.06.115.11 S345.06.215.11
steel st. st.	bulkhead male connection O. D. 12 mm, line S		S345.06.116.11 S345.06.216.11

Components	Steel	Stainless steel ¹⁾
	DIN - Material Number	
Body ²⁾	1.0460	1.4571
Plug	1.4571	
Distance socket	stainless steel	
Indicating dial	1.4301	
Pressure screw	1.0501	1.4571
Insert ring	stainless steel	
Tube fitting and bulkhead male connection	steel	1.4571
Plug seal	PTFE - carbon	
Switch lever	black anodized aluminium	

- **Body:** die-pressed part
- **Surface:** steel phosphatized
- Special types are available

- 1) Can also be supplied for oxygen service. Please notice order instruction B 3! max. working pressure 63 bar max. temperature 60°C
- 2) Available with inspection certificate 3.1 acc. to EN 10 204
- 3) Dimensions acc. to DIN EN 61518 see order instruction B 4