## **CO2 Secure: Real-Time Protection**


## Honeywell





Honeywell's CO<sub>2</sub> Alarm System is the simplest, most reliable way to help protect your employees. Get control over your CO<sub>2</sub> system when you get Honeywell's CO<sub>2</sub> Alarm System. You'll have the confidence of a safer work environment because the CO<sub>2</sub> Alarm System provides two levels of safety warning — both visible and audible. In short, the Honeywell CO<sub>2</sub> Alarm System means added protection for your employees and customers, and it means security for your business.

# **CO2 Alarm System**



P4W-ECC CO<sub>2</sub> Alarm/Strobe

## DISPENSER SAFETY THAT'S INDISPENSABLE

The Honeywell CO<sub>2</sub> Alarm System helps ensure the safety of your employees and customers.

The Honeywell CO<sub>2</sub> Alarm System:

- Can be used as a stand-alone system or, using the 0 – 5 Vdc output, can be integrated into your Honeywell Energy Management System.
- Provides two safety warning levels both visible and audible.
- Offers an additional relay output to a fire alarm at 30,000 ppm CO<sub>2</sub> level.
- Is hard wired for security against tampering.
- Utilizes a power-on sequence that verifies that the system is working properly.
- Features self-diagnostics for when sensor is out of calibration and requires replacement.

#### **Automation and Control Solutions**

In the U.S.: Honeywell 1985 Douglas Drive North Golden Valley, MN 55422-3992

In Canada: Honeywell Limited 35 Dynamic Drive Toronto, Ontario M1V 4Z9

In Latin America: Honeywell 9315 NW 112<sup>th</sup> Avenue Miami, FL 33178 www.honeywell.com

- Includes a self-calibrating sensor that maintains accuracy for up to 15 years.
- Offers a range of warning signs with universal icons and in multiple languages.

### PARTS



 Y7230A: Kits including CO<sub>2</sub> sensor(s) with a range of 0 – 30,000 ppm; 12 Vdc power supply with a button override and CO<sub>2</sub> alarm/strobe(s) with English/ Spanish warning sign



50016094-001: Replacement CO<sub>2</sub> sensor with a range of 0 – 30,000 ppm



- 50016095-001: Replacement 12 Vdc power supply with a button override
- P4W-ECC: Replacement CO2 alarm/strobe

### WARNING SIGNS

A variety of warning signs are also available seperately in packets of 25:

- 63-0225ES: English/Spanish
- 63-0225EI: English/Italian
- 63-0225EG: English/German
- 63-0225EP: English/Portuguese
- 63-0225ED: English/Dutch
- 63-0225EJ: English/Japanese
- 63-0225EC: English/Chinese
- 63-0225EF: English/French Canadian\*
- 63-0225EK: English/Korean

\*Packet also includes 25 product data sheets in French



63-9619 October 2006 © 2006 Honeywell International Inc.