

# Plumbing Code Update


Important New Information For Ontario Contractors

**Honeywell**




## Ontario Has Adopted The 2005 National Plumbing Code of Canada (Modified).


Any New Residential Or Commercial Construction Must Comply To The New Codes. Honeywell Thermostatic Mixing Valves Meet These Requirements.




*The AMX mixing valve cuts installation time and number of parts in half.*








*AM-1 mixing valve installation.*



*UMV-304 3-Port Option Typically used in public facilities and office buildings where a consistent temperature is required.*



*UMV-304 4-Port Option Typically used in homes, apartments, hotels and locations where the user is free to adjust the water temperature.*

	AMX Series	MX Series	AM1070 Series	AM-1 Series	UMV-304U
					
Designed To Help Prevent Scalding — An important health feature your customers will appreciate	•	•	•	•	•
Teflon® Coating — Reduces clogging, which means fewer callbacks	•	•	•	•	
Easy Installation — A Thermostrip® is included to make temperature-setting easy for one person	•		•	•	
Built-In Check Valves — Prevent cross-flow of hot water	•		•	• <small>(union models only)</small>	•
High Cv Ratings — Ensures larger flow through the valve	4	4 – 50	1.8	3.2 – 4.3	0.55
Certification	ASSE 1017	ASSE 1017	ASSE 1070 & 1017	ASSE 1017	ASSE 1016 & 1070

## Ontario Codes

- 7.6.5. Water Temperature Control
- 7.6.5.1. Maximum Temperature of Hot Water — *(Use AM-1, AM 1070, AMX, MX or UMV Series to meet this code.)*
- Except as provided in Sentences (2) and 7.6.5.3.(1), the maximum temperature of hot water supplied by fittings to fixtures in a residential occupancy shall not exceed 49°C.
  - Sentence (1) does not apply to hot water supplied to installed dishwashers or clothes washers.
- 7.6.5.3. Temperature Control Devices — *(Use AM-1, AM 1070, AMX, MX or UMV Series to meet this code.)*
- A water distribution system supplying hot water to any bathtub, shower or hand basin that is accessible to a patient or resident in a Group B, Division 2 or 3 occupancy or a resident of a group home, home for special care or residence for developmentally-handicapped adults shall have one or more temperature gauges and control devices that are,
    - accessible only to supervisory staff, and
    - capable of being adjusted to ensure that the temperature of the water supplied to the fixtures does not exceed 49°C.