

блоки аварийного питания
для светильников эвакуационного освещения

■ Таблица выбора коэффициента светового потока лампы
в режиме питания от резервного источника

Лампа	Мощность	Коэффициент светового потока						
		618 40	618 42	618 46	618 48	6640 70	6640 71	
T8 	18 W	0.35	0.95	0.45	0.32	0.10		
	36 W	0.16	0.41	0.18	0.14		0.07	
	58 W	-	0.33	0.15	0.11			
T5 	14 W	0.29	0.65	0.48	0.22			
	21 W	0.25	0.56	0.26	0.19			
	24 W	0.24	0.53	0.24	0.18			
	28 W	0.22	0.50	0.22	0.17			
	35 W							
	49 W		0.39	0.18	0.13			
	54 W		0.38	0.17	0.12			
PLC 	10 W					0.16		
	13 W						0.14	
	18 W						0.10	
	26 W						0.08	
PLL 	18 W	0.35	0.92	0.44	0.32	0.09		
	24 W	0.21	0.53 ⁽²⁾	0.23 ⁽²⁾	0.18		0.08	
	36 W	0.18	0.43 ⁽²⁾	0.20 ⁽¹⁾	0.14		0.06	
	40 W	0.18 ⁽³⁾	0.49	0.22	0.16			
	55 W	0.13 ⁽³⁾	0.36	0.16	0.12			
PLT 	18 W						0.10	
	26 W						0.08	
	32 W						0.07	
	42 W							
2D 	10 W		0.40 ⁽¹⁾	0.88	0.14	0.19		
	16 W	0.48 ⁽¹⁾	0.90 ⁽²⁾	0.42 ⁽²⁾	0.30		0.12	
	21 W	0.40	0.76 ⁽²⁾	0.33 ⁽²⁾	0.25		0.10	
	28 W	0.31	0.61 ⁽²⁾	0.28 ⁽²⁾	0.20		0.07	
	38 W	0.26	0.57	0.20	0.19		0.06	
	55 W	-	-	-	-			
C 	22 W	0.35	0.76	0.35	0.25			
	32 W	0.24	0.53	0.24	0.18			
	40 W	0.19	0.42 ⁽¹⁾	0.19 ⁽²⁾	0.14			

(1) Автономность до 1ч30мин
(2) Автономность до 1ч45мин
(3) Автономность до 45мин
(4) Нужно снять выключатель

■ Аккумуляторы

Кат. №	Вид аккумулятора	Характеристики аккумулятора
618 40	Ni-Cd	6.0 V - 1.5 Ah
618 42	Ni-Cd	7.2 V - 4 Ah
618 46	Ni-Cd	3.6 V - 4 Ah
618 48	Ni-Cd	7.2 V - 4 Ah
664 070	Ni-Cd	3.6 V - 4/4.5 Ah
664 071	Ni-Cd	4.8 V - 4/4.5 Ah
664 072	Ni-Cd	6.0 V - 4/4.5 Ah
664 073	Ni-Cd	4.8 V - 4/4.5 Ah
664 074	Ni-Cd	7.2 V - 4/4.5 Ah
664 075	Ni-Cd	4.8 V - 1.5/1.6 Ah
664 076	Ni-Cd	6.0 V - 1.5/1.6 Ah
664 077	Ni-Cd	8.4 V - 1.5/1.6 Ah
664 078	Ni-Cd	9.6 V - 1.5/1.6 Ah
664 079	Ni-Cd	13.2 V - 1.5/1.6 Ah
664 080	Ni-Cd	9.6 V - 1.5 Ah
664 081	Ni-Cd	9.6 V - 4 Ah

Коэффициент светового потока									
	6640 72	6640 73	6640 74	6640 75	6640 76	6640 77	6640 78	6640 79	6640 80/81
				0.11					0.34
					0.06				0.18
	0.05					0.05			0.10
		0.19					0.33		0.49
		0.18					0.32		0.36
		0.14					0.27		0.29
			0.18					0.28	0.25
			0.17 ⁽⁴⁾					0.23 ⁽⁴⁾	
			0.11 ⁽⁴⁾					0.17 ⁽⁴⁾	
			0.09 ⁽⁴⁾					0.14 ⁽⁴⁾	0.14
				0.20					0.63
					0.14				0.44
					0.10				0.41
	0.09				0.07	0.10			0.23
				0.11					0.38
					0.07				0.28
	0.06				0.05	0.08			0.19
	0.05					0.05			0.12
					0.10				0.32
	0.08				0.07	0.10			0.25
	0.08				0.07	0.09			0.19
	0.07					0.07			0.15
				0.07					0.70
					0.12				0.35
					0.09				0.35
	0.08				0.08	0.10			0.24
	0.06				0.05	0.07			0.18
	0.04					0.05			0.11