

- Single turn resolution  $\leq 10$  bit
- Robust design
- Shock and vibration protected




## Technical data

Operating temperature	-40 °C .. +80 °C
Ingress protection class [IEC 60529]	IP67/IP66 (Encoder body/Shaft inlet)
Current consumption	40 mA at 24 Vdc
Vibration [IEC 60068-2-6]	$\leq 300$ m/s <sup>2</sup>
Shock [IEC 60068-2-27]	$\leq 2000$ m/s <sup>2</sup>
Cover material	Aluminium
Weight	300 g
Shaft load (axial/radial)	50 N / 60 N
Shaft material	Stainless steel
Rotational speed max	6000 rpm
Polarity protected	Yes

## Encoder configuration

Type	RSA
Model	506 Singleturn
Shaft type	Ø10 with partial flat
Flange type	Clamping flange (61-type)
Resolution	10 bit singleturn
Power supply	9-36 Vdc
Output signal	Analogue 4-20 mA
Connection type	M12 connector 8-pin
Connecting direction	Axial
Active angle	50.0

**Dimensions****Output signals****Pin configuration**

Function	Pin
+E Volt	8
0 Volt	7
I out	5
Preset	3
Code sequence	6
Case	Housing

**Ordering information**

Part number

1070422-01