

- 58mm diameter
- Extremely robust design
- Shock and vibration protected
- Inductive scanning



Technical data

| | |
|--------------------------------------|-------------------------|
| Operating temperature | -40 °C .. +70 °C |
| Ingress protection class [IEC 60529] | IP67 |
| Current consumption | 100 mA at 24 Vdc |
| Vibration [IEC 60068-2-6] | ≤ 300 m/s ² |
| Shock [IEC 60068-2-27] | ≤ 2000 m/s ² |
| Cover material | Aluminium (anodized) |
| Weight | 430 g |
| Shaft load (axial/radial) | 100 / 125 N |
| Shaft material | Stainless steel |
| Rotational speed max | 12000 rpm |
| Polarity protected | Yes |

Encoder configuration

| | |
|----------------------|---|
| Type | ISA |
| Model | 608 Multiturn |
| Shaft type | ø10mm shaft with face |
| Flange type | Clamping flange (61sp-type) |
| Resolution | 25 bit (13 bit singleturn + 12 bit multiturn) |
| Power supply | 9-36 Vdc |
| Output signal | PROFINET |
| Connection type | 3xM12 connectors |
| Connecting direction | Radial |

Dimensions

Drawing available upon request to Leine & Linde.

Output signals

Pin configuration

| Function | Pin |
|-------------------------|-----|
| 4p D-coded M12 (Port 2) | |
| Tx+ | 1 |
| Rx+ | 2 |
| Tx- | 3 |
| Rx- | 4 |
| 4p D-coded M12 (Port 1) | |
| Tx+ | 1 |
| Rx+ | 2 |
| Tx- | 3 |
| RX- | 4 |
| 4p A-coded M12 (Supply) | |
| +E Volt | 1 |
| 0 Volt | 3 |

Ordering information

Part number 1071032-01