



- Robust encoder in compact design
- Total build length 55 mm
- Through-going hollow shaft with insulated peek insert



Technical data

| | |
|--------------------------------------|--|
| Operating temperature | -40 °C 100 °C |
| Ingress protection class [IEC 60529] | IP67 (IP66 at shaft inlet) |
| Vibration [IEC 60068-2-6] | ≤ 200 m/s ² |
| Shock [IEC 60068-2-27] | ≤ 1500 m/s ² |
| Cover material | Aluminium (anodized) |
| Weight | 1000 g |
| Shaft load (axial/radial) | 50 N / 100 N |
| Rotational speed max | 6000 rpm |
| Shaft material | Stainless steel with insulated peek insert |
| Short circuit protected | Yes |
| Polarity protected | Yes |
| Current consumption | 60 mA at 24 Vdc (Max. 80 mA) |
| Output load | ± 40 mA |
| Output frequency max | 200 kHz |
| Cable length max | 100 m at 100 kHz |
| Channel separation | 90 °el ± 25 °el |
| Dividing error | 50 °el |

Encoder configuration

| | |
|----------------------|---------------------------------------|
| Type | CHI |
| Model | 703 |
| Shaft type | Ø12 mm through-going hollow shaft |
| Flange type | 87-flange |
| Resolution | 2048 |
| Power supply | 5-30 Vdc |
| Output signal | HTL |
| Connection type | M23 connector 12-pin |
| Connecting direction | Radial |
| Pin layout | CCW |
| Torque support | Tether arm with insulated peek insert |

