

- Single turn resolution ≤ 10 bit
- Robust design
- Shock and vibration protected



Technical data

Operating temperature	-40 °C .. +80 °C
Ingress protection class [IEC 60529]	IP67/IP66 (Encoder body/Shaft inlet)
Current consumption	40 mA at 24 Vdc
Vibration [IEC 60068-2-6]	≤ 300 m/s ²
Shock [IEC 60068-2-27]	≤ 2000 m/s ²
Cover material	Aluminium
Weight	300 g
Shaft load (axial/radial)	50 N / 60 N
Shaft material	Stainless steel
Rotational speed max	6000 rpm
Polarity protected	Yes

Encoder configuration

Type	RSA
Model	506 Singleturn
Shaft type	Ø10 mm round
Flange type	Clamping flange (61-type)
Resolution	10 bit singleturn
Power supply	9-30 Vdc
Output signal	Parallel Gray (Sink)
Connection type	M23 connector 17-pin
Connecting direction	Radial

Dimensions

Drawing available upon request to Leine & Linde.

Output signals

Pin configuration

Function	Pin
Bit 1	1
Bit 2	2
Bit 3	3
Bit 4	4
Bit 5	5
Bit 6	6
Bit 7	7
Bit 8	8
Bit 9	9
Bit 10	10
/Hold	13
Code sequence	14
0 Volt	15
+E Volt	16
Chassis	Shield

Ordering information

Part number

738667-01