

Ruggedized Shaft encoder, Absolute

- 58mm diameter
- Single turn resolution 13 bit
- Multi turn resolution 12 bit
- Robust design
- Shock and vibration protected

**Technical data**

Operating temperature	-40 °C .. +70 °C
Ingress protection class [IEC 60529]	IP67/IP66 (Encoder body/Shaft inlet)
Current consumption	65 mA at 24 Vdc (Max. 100 mA at 24 Vdc)
Vibration [IEC 60068-2-6]	≤ 300 m/s ²
Shock [IEC 60068-2-27]	≤ 1000 m/s ²
Cover material	Aluminium (Passivated and coated)
Weight	300 g
Shaft load (axial/radial)	50 N / 60 N
Shaft material	Stainless steel
Rotational speed max	12000 rpm
Polarity protected	Yes

Encoder configuration

Type	RSA
Model	608 Multiturn
Shaft type	Ø10 mm round
Flange type	Synchro flange (63-type)
Resolution	25 bit absolute + Incremental 1024 ppr RS422
Power supply	9-30 Vdc
Output signal	SSI Gray with additional incremental RS422 signals
Connection type	M23 connector 17-pin
Connecting direction	Radial

Dimensions

Drawing available upon request to Leine & Linde.

Output signals

Pin configuration

Function	Pin
Code sequence	2
STATUS	3
PRESET	5
+E Volt	7
Clock	8
Clock\	9
0 Volt	10
S90	12
S90\	13
Data	14
S00	15
S00\	16
Data\	17

Ordering information

Part number

760229-02