


Model Number

IA5-18GM-I3

Features

- Inductive analog
- Output 0 mA ... 20 mA
- Flush mounting

Connection




Accessories

BF 18

Mounting flange, 18 mm

Dimensions



Technical Data

General specifications

Switching element function	Analog current output
Installation	flush
Output polarity	DC
Measurement range	2 ... 5 mm

Nominal ratings

Operating voltage	U_B	15 ... 30 V
Repeat accuracy		$\pm 6 \mu\text{m}$
No-load supply current	I_0	$\leq 10 \text{ mA}$

Analog output

Output type	0 ... 20 mA
Linearity error	$\leq \pm 10 \%$ of full-scale value
Load resistor	$\leq 500 \Omega$
Rate of current rise	
0 ... 20 mA	max. 5.1 A/s
20 ... 0 mA	max. 4 A/s
Recovery time	1 ... 10 ms, typ. 5 ms
Adjustment tolerance zero point	$\leq \pm 10 \%$ of full-scale value
Temperature drift	$\leq \pm 0.1 \%$ /K of full-scale value
Operating voltage	$\leq 1 \%$
Residual ripple	$\pm 30 \mu\text{A}$

Ambient conditions

Ambient temperature	-10 ... 70 °C (14 ... 158 °F)
---------------------	-------------------------------

Mechanical specifications

Connection type	cable PVC, 2 m
Core cross-section	0.5 mm ²
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67

Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007 EN 60947-5-7:2003 IEC 60947-5-7:2003

Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of $\leq 36 \text{ V}$ do not bear a CCC marking because they do not require approval.