




Model Number

NBB1,5-8GM40-Z0-V3

Features

- Basic series
- 1.5 mm embeddable

Connection



Pinout




Wire colors in accordance with EN 60947-5-2

1	BN
3	BU
4	BK

Release date: 2009-05-28 16:04 Date of issue: 2009-05-28 031943_ENG.xml

Dimensions



Technical Data

General specifications

Switching element function	DC	Make function
Rated operating distance	s_n	1.5 mm
Installation		embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 1.21 mm
Reduction factor r_{Al}		0.4
Reduction factor r_{Cu}		0.35
Reduction factor r_{V2A}		0.8
Reduction factor r_{Brass}		0.5

Nominal ratings

Operating voltage	U_B	6 ... 60 V
Switching frequency	f	0 ... 2000 Hz
Hysteresis	H	1 ... 10 typ. 3 %
Reverse polarity protection		tolerant
Short-circuit protection		no
Voltage drop	U_d	≤ 6 V
Operating current	I_L	4 ... 100 mA
Off-state current	I_r	0 ... 1 mA typ. 0.7 mA
Indication of the switching state		LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	V3-connector
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67