




Model Number

NJ1,5-8GM50-E

Features

- Comfort series
- 1.5 mm embeddable

Connection



Accessories


EXG-08

Mounting aid

BF 8

Mounting flange

Dimensions



Technical Data

General specifications

Switching element function		NPN Make function
Rated operating distance	s_n	1.5 mm
Installation		embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 1.215 mm
Reduction factor r_{Al}		0.24
Reduction factor r_{Cu}		0.21
Reduction factor r_{V2A}		0.67

Nominal ratings

Operating voltage	U_B	10 ... 60 V
Switching frequency	f	0 ... 5000 Hz
Hysteresis	H	1 ... 15 typ. 5 %
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 2.6 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.01 mA
No-load supply current	I_0	≤ 10 mA
Indication of the switching state		LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
Storage temperature	-40 ... 85 °C (233 ... 358 K)

Mechanical specifications

Connection type	2 m, PUR cable
Core cross-section	0.14 mm ²
Housing material	Stainless steel
Sensing face	LCP
Protection degree	IP67

Approvals and certificates

CCC approval	Certified by China Compulsory Certification (CCC)
--------------	---