




Model Number

NBN2-8GM50-E2-V3

Features

- Basic series
- 2 mm not embeddable

Connection



Pinout



Wire colors in accordance with EN 60947-5-2

1	BN
3	BU
4	BK

Accessories

BF 8

Mounting flange

V3-WM

Cable connector

V3-GM

Cable connector


V3-WM-2M-PUR

Cable connector

V3-GM-2M-PUR

Cable connector

Dimensions



Technical Data

General specifications

Switching element function	PNP	Make function
Rated operating distance	s_n	2 mm
Installation		not embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 1.62 mm
Reduction factor r_{Al}		0.45
Reduction factor r_{Cu}		0.35
Reduction factor r_{V2A}		0.75

Nominal ratings

Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 1500 Hz
Hysteresis	H	typ. 5 %
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0	≤ 15 mA
Indication of the switching state		LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	V3-connector
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67

Release date: 2009-11-11 16:39 Date of issue: 2009-11-11 083612_ENG.xml