



CE

General specifications	
Switching element function	NPN Make function
Rated operating distance $s_n$	10 mm
Installation	embeddable
Assured operating distance $s_a$	0 ... 8.1 mm
Reduction factor $r_{Al}$	0.3
Reduction factor $r_{Cu}$	0.2
Reduction factor $r_{V2A}$	0.6
Nominal ratings	
Operating voltage $U_B$	10 ... 30 V
Switching frequency $f$	0 ... 10 Hz
Reverse polarity protection	protected against reverse polarity
Short-circuit protection	pulsing
Voltage drop $U_d$	$\leq 3$ V
Operating current $I_L$	0 ... 200 mA
Off-state current $I_r$	0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current $I_0$	$\leq 15$ mA
Constant magnetic field $B$	100 mT
Alternating magnetic field $B$	100 mT
Indication of the switching state	LED, yellow
Standard conformity	
Standards	IEC / EN 60947-5-2:2004
Ambient conditions	
Ambient temperature	-25 ... 70 °C (248 ... 343 K)
Mechanical specifications	
Connection type	2 m, PVC cable
Core cross-section	0.34 mm <sup>2</sup>
Housing material	brass, teflon coated
Sensing face	PPS
Protection degree	IP67

Connection type:

