


**Model Number****NBN2-8GM40-Z0****Features**


- Basic series
- 2 mm not embeddable

**Connection****Accessories****BF 8**

Mounting flange

**EXG-08**

Mounting aid

**Dimensions****Technical Data****General specifications**

Switching element function	DC	Make function
Rated operating distance	$s_n$	2 mm
Installation	not embeddable	
Output polarity	DC	
Assured operating distance	$s_a$	0 ... 1.62 mm
Reduction factor $r_{Al}$	0.4	
Reduction factor $r_{Cu}$	0.39	
Reduction factor $r_{V2A}$	0.75	

**Nominal ratings**

Operating voltage	$U_B$	5 ... 60 V
Switching frequency	$f$	0 ... 1200 Hz
Hysteresis	$H$	1 ... 10 typ. 5 %
Reverse polarity protection	tolerant	
Short-circuit protection	pulsing	
Voltage drop	$U_d$	$\leq 5$ V
Operating current	$I_L$	2 ... 100 mA
Off-state current	$I_r$	0 ... 0.5 mA typ.
Indication of the switching state	LED, yellow	

**Standard conformity**

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

**Mechanical specifications**

Connection type	2 m, PVC cable
Core cross-section	0.14 mm <sup>2</sup>
Housing material	Stainless steel
Sensing face	PBT
Protection degree	IP67

**Approvals and certificates**

CCC approval	Certified by China Compulsory Certification (CCC)
--------------	---