




Model Number

NBB2-6,5M30-E2-5M

Features

- Basic series
- 2 mm embeddable
- Increased operating distance

Connection




Accessories

BF 6,5

Mounting flange, 6.5 mm

Dimensions



Technical Data

General specifications

| | | |
|----------------------------|-------|---------------|
| Switching element function | PNP | NO |
| Rated operating distance | s_n | 2 mm |
| Installation | | embeddable |
| Output polarity | | DC |
| Assured operating distance | s_a | 0 ... 1.62 mm |
| Reduction factor r_{AI} | | 0.45 |
| Reduction factor r_{Cu} | | 0.4 |
| Reduction factor r_{V2A} | | 0.75 |

Nominal ratings

| | | |
|-----------------------------------|-------|--|
| Operating voltage | U_B | 10 ... 30 V |
| Switching frequency | f | 0 ... 3000 Hz |
| Reverse polarity protected | | reverse polarity protected |
| Short-circuit protection | | pulsing |
| Voltage drop | U_d | ≤ 3 V |
| Operating current | I_L | 0 ... 100 mA |
| Off-state current | I_r | 0 ... 0.5 mA typ. 0.1 μ A at 25 °C |
| No-load supply current | I_0 | ≤ 15 mA |
| Indication of the switching state | | LED, yellow |

Ambient conditions

| | |
|---------------------|--------------------------------|
| Ambient temperature | -25 ... 70 °C (-13 ... 158 °F) |
|---------------------|--------------------------------|

Mechanical specifications

| | |
|--------------------|----------------------|
| Connection type | cable PVC, 5 m |
| Core cross-section | 0.14 mm ² |
| Housing material | brass, nickel-plated |
| Sensing face | LCP |
| Protection degree | IP67 |

Compliance with standards and directives

| | |
|---------------------|---|
| Standard conformity | |
| Standards | EN 60947-5-2:2007 IEC 60947-5-2:2007 |

Approvals and certificates

| | |
|--------------|--|
| UL approval | cULus Listed, General Purpose |
| CSA approval | cCSAus Listed, General Purpose |
| CCC approval | Products with a maximum operating voltage of ≤ 36 V do not bear a CCC marking because they do not require approval. |