




Model Number

NCB1,5-8GM40-Z1

Features

- 1.5 mm embeddable
- 2-wire DC

Connection



Accessories


EXG-08

Quick mounting bracket with dead stop

BF 8

Mounting flange, 8 mm

Dimensions



Technical Data

General specifications

Switching element function	DC	NC
Rated operating distance	s_n	1.5 mm
Installation	embeddable	
Output polarity	DC	
Assured operating distance	s_a	0 ... 1.21 mm
Reduction factor r_{Al}	0.22	
Reduction factor r_{Cu}	0.16	
Reduction factor r_{V2A}	0.64	

Nominal ratings

Operating voltage	U_B	5 ... 60 V
Switching frequency	f	0 ... 1200 Hz
Hysteresis	H	1 ... 10 typ. 5 %
Reverse polarity protected	tolerant	
Short-circuit protection	pulsing	
Voltage drop	U_d	≤ 5 V
Operating current	I_L	2 ... 100 mA
Lowest operating current	I_m	2 mA
Off-state current	I_r	0 ... 0.5 mA typ.
Indication of the switching state	LED, yellow	

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Connection type	cable PUR, 2 m
Core cross-section	0.14 mm ²
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	LCP
Protection degree	IP67

Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Certified by China Compulsory Certification (CCC)