


**Model Number**


NCB5-18GM40-Z0-10M

**Connection****Accessories****BF 18**

Mounting flange, 18 mm

**EXG-18**

Quick mounting bracket with dead stop

**Dimensions****Technical Data****General specifications**

Switching element function	DC	NO
Rated operating distance	$s_n$	5 mm
Installation	embeddable	
Output polarity	DC	
Assured operating distance	$s_a$	0 ... 4.05 mm
Reduction factor $r_{AI}$	0.37	
Reduction factor $r_{Cu}$	0.33	
Reduction factor $r_{304}$	0.7	

**Nominal ratings**

Operating voltage	$U_B$	5 ... 60 V
Switching frequency	$f$	0 ... 350 Hz
Hysteresis	$H$	1 ... 10 typ. 5 %
Reverse polarity protected	tolerant	
Short-circuit protection	pulsing	
Voltage drop	$U_d$	$\leq 5$ V
Operating current	$I_L$	2 ... 100 mA
Lowest operating current	$I_m$	2 mA
Off-state current	$I_r$	0 ... 0.5 mA typ.
Indication of the switching state	all direction LED, yellow	

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

**Mechanical specifications**

Connection type	cable PUR, 10 m
Cable version	PA
Core cross-section	0.34 mm <sup>2</sup>
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Protection degree	IP67

**Compliance with standards and directives**

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

**Approvals and certificates**

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Certified by China Compulsory Certification (CCC)