


**Model Number**

NBB8-18GM30-E2-V1-M

Features

- Basic series
- 8 mm embeddable
- increased operating distance
- e1-Type approval

Connection**Accessories****BF 18-F**

Mounting flange

EXG-18

Mounting aid

V1-G

Non pre-wired cable socket

V1-W


Non pre-wired cable socket

V1-G-2M-PUR

Cable connector

V1-W-2M-PUR

Cable connector

Dimensions**Technical Data****General specifications**

Switching element function		PNP Make function
Rated operating distance	s_n	8 mm
Installation		embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 6.48 mm
Reduction factor r_{AI}		0.45
Reduction factor r_{Cu}		0.4
Reduction factor r_{V2A}		0.7

Nominal ratings

Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 500 Hz
Hysteresis	H	typ. 5 %
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0	≤ 15 mA
Indication of the switching state		LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	V1-connector
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67

Approvals and certificates

e1 Type approval	95/54/EC
------------------	----------