




Model Number

NRN6-8GM40-E2-V1


Features

- Reduction factor = 1
- 6 mm not embeddable
- Magnetic field resistant

Connection



Dimensions



Technical Data

General specifications

Switching element function	PNP Make function
Rated operating distance	s_n 6 mm
Installation	not embeddable
Output polarity	DC
Assured operating distance	s_a 0 ... 4.86 mm
Reduction factor r_{Al}	1
Reduction factor r_{Cu}	1
Reduction factor r_{V2A}	1

Nominal ratings

Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 400 Hz
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0	≤ 15 mA
Indication of the switching state		Multihole-LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	V1-connector
Housing material	brass, nickel-plated
Sensing face	Crastin (PBTB)
Protection degree	IP67