




Model Number

V3-GM-1,5M-PUR-V3-GM
 Connecting cable, M8 to M8, PUR cable 3-pin

Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold-plated and machined contacts
- Halogen-free
- Suitable for 2- and 3-wire technology


Dimensions



Technical data

General specifications		
Number of pins		3
Connection 1		female connector
Construction type 1		straight
Threading 1		M8
Connection 2		Male connector
Construction type 2		straight
Threading 2		M8
Electrical specifications		
Operating voltage	U _B	max. 60 V DC
Test voltage		> 1500 V _{eff} AC
Operating current		max. 4 A
Volume resistance		< 5 mΩ
Ambient conditions		
Ambient temperature		-25 ... 100 °C (-13 ... 212 °F) for temperatures over 80 °C (176 °F) reduced elongation at tear
Pollution Degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		1 mm
Protection degree		IP67
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, green
Cable		PUR
Slotted nut		Diecast zinc
Sleeve connector		Diecast zinc
Core insulation		PP
Cable		
Sheath diameter		Ø4.8 mm
Bending radius		> 10 x cable diameter, appropriate for conveyor chains
Color		grey
Cores		3 x 0.34 mm ²
Conductor construction		19 x 0.15 mm Ø
Length	L	1.5 m
Flammability		
Contact material		94 V-2
Housing		94 V-2

Electrical connection



Release date: 2012-01-19 11:06 Date of issue: 2012-01-19 211465_eng.xml