




### Model Number

NJ10-30GM50-A2-10M

### Features

- Stainless steel housing
- 10 mm flush

### Connection



### Accessories


#### BF 30

Mounting flange, 30 mm

#### EXG-30

Quick mounting bracket with dead stop

### Dimensions



### Technical Data

#### General specifications

Switching element function		PNP	NO/NC
Rated operating distance	$s_n$	10 mm	
Installation		flush	
Output polarity		DC	
Assured operating distance	$s_a$	0 ... 8.1 mm	
Reduction factor $r_{Al}$		0.2	
Reduction factor $r_{Cu}$		0.15	
Reduction factor $r_{304}$		0.6	

#### Nominal ratings

Operating voltage	$U_B$	10 ... 60 V	
Switching frequency	$f$	0 ... 300 Hz	
Hysteresis	$H$	typ. 5 %	
Reverse polarity protection		reverse polarity protected	
Short-circuit protection		pulsing	
Voltage drop	$U_d$	$\leq 3$ V	
Operating current	$I_L$	0 ... 400 mA	
No-load supply current	$I_0$	$\leq 15$ mA	
Indication of the switching state		LED, yellow	

#### Functional safety related parameters

MTTF <sub>d</sub>	1190 a
Mission Time ( $T_M$ )	20 a
Diagnostic Coverage (DC)	0 %

#### Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

#### Mechanical specifications

Connection type	cable PVC, 10 m
Core cross-section	0.75 mm <sup>2</sup>
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PBT
Protection degree	IP67

#### Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

#### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSAus approval	cCSAus Listed, General Purpose