




Model Number

NEB6-12GM50-E3-V1


Features

- Increased operating distance
- 6 mm embeddable

Connection



Pinout




Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Accessories

- BF 12**
Mounting flange, 12 mm
- V1-G**
4-pin, M12 female field-attachable connector
- V1-W**
4-pin, M12 female field-attachable connector
- V1-G-2M-PUR**
Cable socket, M12, 4-pin, PUR cable
- V1-W-2M-PUR**
Cable socket, M12, 4-pin, PUR cable

Dimensions



Technical Data

General specifications

Switching element function	PNP	NC
Rated operating distance	s_n	6 mm
Installation		quasi embedd.
Output polarity		DC
Assured operating distance	s_a	0 ... 4.8 mm
Actuating element		structural steel, e. g. 1.0037, SR235JR (formerly St37-2) 18 mm x 18 mm x 1 mm
Reduction factor r_{Al}		0.28
Reduction factor r_{Cu}		0.2
Reduction factor r_{304}		0.7
Reduction factor r_{Brass}		0.35

Nominal ratings

Installation conditions	
A	in steel 1.0037 (St37): 2.4 mm in other metal: 1.2 mm
B	12 mm
C	18 mm
F	24 mm
Operating voltage	U_B 10 ... 30 V DC
Switching frequency	f 0 ... 800 Hz
Hysteresis	H 0.06 ... 1.2 mm
Reverse polarity protected	yes
Short-circuit protection	pulsing
Overload resistance	yes
Wire breakage protection	yes
Surge suppression	yes
Ripple	10 %
Voltage drop	U_d ≤ 2 V
Repeat accuracy	0.3 mm
Operating current	I_L 0 ... 200 mA, above 70 °C (158 °F) ≤ 150 mA
Off-state current	I_r ≤ 10 μ A
No-load supply current	I_0 ≤ 15 mA
Indication of the switching state	LED, yellow

Functional safety related parameters

MTTF _d	1740 a
Mission Time (T _M)	20 a
Diagnostic Coverage (DC)	0 %

Ambient conditions

Ambient temperature	-25 ... 85 °C (-13 ... 185 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)

Mechanical specifications

Connection type	Device connector M12 x 1, 4-pin
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67
Mass	20 g

Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

Approvals and certificates

UL approval	cULus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of ≤ 36 V do not bear a CCC marking because they do not require approval.

Release date: 2012-02-08 15:32 Date of issue: 2012-02-08 231716_eng.xml

Installation conditions

