




**Model Number**

NBN3-8GM25-E0-V3

**Features**

- Basic series
- 3 mm not embeddable
- Increased operating distance

**Connection**



**Pinout**




Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

**Accessories**

- BF 8**  
Mounting flange, 8 mm
- V3-GM**  
Female connector, M8, 3-pin, field attachable
- V3-WM**  
Female connector, M8, 3-pin, field attachable
- V3-GM-2M-PUR**  
Cable socket, M8, 3-pin, PUR cable
- V3-WM-2M-PUR**  
Cable socket, M8, 3-pin, PUR cable

**Dimensions**



**Technical Data**

**General specifications**

Switching element function		NPN	NO
Rated operating distance	$s_n$	3 mm	
Installation		not embeddable	
Output polarity		DC	
Assured operating distance	$s_a$	0 ... 2.43 mm	
Reduction factor $r_{AI}$		0.45	
Reduction factor $r_{Cu}$		0.35	
Reduction factor $r_{303}$		0.7	

**Nominal ratings**

Operating voltage	$U_B$	5 ... 30 V
Switching frequency	$f$	0 ... 2000 Hz
Short-circuit protection		pulsing
Voltage drop	$U_d$	$\leq 2.5$ V
Operating current	$I_L$	0 ... 100 mA
Off-state current	$I_r$	0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current	$I_0$	$\leq 15$ mA
Indication of the switching state		Multihole-LED, yellow

**Functional safety related parameters**

MTTF <sub>d</sub>	1870 a
Mission Time (T <sub>M</sub> )	20 a
Diagnostic Coverage (DC)	0 %

**Ambient conditions**

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

**Mechanical specifications**

Connection type	Device connector M8 x 1, 3-pin
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67

**Compliance with standards and directives**

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

**Approvals and certificates**

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of $\leq 36$ V do not bear a CCC marking because they do not require approval.

Release date: 2011-07-07 14:19 Date of issue: 2011-07-07 802841\_eng.xml