




Model Number

NBN15-30GK60-AR-3M

Features

- Relay output
- Sensing range 15 mm
- SPDT output
- Switch load currents to 6 Amps

Connection



Accessories


BF 30

Mounting flange, 30 mm

AB-30

Mounting aid

Dimensions



Technical Data

General specifications

Switching element function		SPDT Relay
Rated operating distance	s_n	15 mm
Installation		not embeddable
Output polarity		DC
Reduction factor r_{AI}		0.4
Reduction factor r_{Cu}		0.37
Reduction factor r_{304}		0.73
Mechanical life		2×10^7 operations

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC
-------------------	-------	----------------

Switching frequency	f	5 Hz
Hysteresis	H	3 ... 15 % , typ. 5 %
Reverse polarity protected		yes
Short-circuit protection		no
Operating current	I_L	6 A max.
No-load supply current	I_0	≤50 mA
Indication of the switching state		LED, yellow
Contact resistance		28 V DC/6 A resistive; 250 V AC/6A resistive

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-40 ... 70 °C (-40 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Housing material	PBT
Sensing face	PBT
Protection degree	IP68

Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose