




### Model Number

NMB3-8GM35-E0-150MM-V3

### Features

- 3 mm flush
- Stainless steel sensing face
- Increased operating distance

### Connection



### Pinout



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

### Accessories


#### V3-GM-2M-PUR

Cable socket, M8, 3-pin, PUR cable

#### V3-WM-2M-PUR

Cable socket, M8, 3-pin, PUR cable

### Dimensions



### Technical Data

#### General specifications

Switching element function		NPN	NO
Rated operating distance	$s_n$	3 mm	
Installation		flush	
Output polarity		DC	
Assured operating distance	$s_a$	0 ... 2.43 mm	
Reduction factor $r_{Al}$		0.3	
Reduction factor $r_{Cu}$		0.2	
Reduction factor $r_{304}$		0.7	

#### Nominal ratings

Operating voltage	$U_B$	10 ... 30 V
Switching frequency	$f$	0 ... 360 Hz
Hysteresis	$H$	5 ... 15 typ. 10 %
Reverse polarity protection		yes
Short-circuit protection		yes
Voltage drop	$U_d$	$\leq 2$ V
Operating current	$I_L$	0 ... 100 mA
Off-state current	$I_r$	0 ... 10 $\mu$ A typ. 0.1 $\mu$ A at 25 °C
No-load supply current	$I_0$	$\leq 10$ mA

#### Indicators/operating means

Operating display	Dual LED
	Green: power
	Yellow: output

#### Standard conformity

Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007
-----------	-----------------------------------------

#### Ambient conditions

Ambient temperature	-25 ... 75 °C (-13 ... 167 °F)
---------------------	--------------------------------

#### Mechanical specifications

Connection type	Cable connector M8 x 1, PUR 150 mm
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	Stainless steel 1.4305 / AISI 303
Protection degree	IP67

#### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of $\leq 36$ V do not bear a CCC marking because they do not require approval.