

Features

- Extended temperature range for indoor/outdoor use
- Fiber or Cat5 KVM communication for keyboard and touchscreen
- Modular design for field maintainability
- Solution for Div 2 and Safe Areas
- Variety of keyboard and mounting options
- Watershed housing allows for proper drainage
- Widescreen 16:10 aspect ratio


Application

The VisuNet IND Edge is a universal design that is well suited for many applications. Unit features a hazardous area KVM for keyboard and touchscreen inputs. The intrinsically safe touchscreen properly protects the touchscreen interface.

Specifically designed for manufacturing environments where dust, bacteria, water, and other undesirable materials might accumulate, the sloped enclosure provides washdown solutions with proper drainage to prevent standing water. The formed lip enclosure opening prevents the flow of liquid or other contaminants from entering the enclosure.



Dimensions



General specifications	
Distance	Transmitter "K3": 300 m (1000 ft) Transmitter "K4": 120 m (400 ft) Transmitter "K5": 200 m (650 ft), 62.5 μ multimode; 400 m (1300 ft), 50.0 μ multimode
Supply	
Connection	Monitor: power, CAT5, fiber (LC)
Power consumption	Main unit: 60 W max, 100 ... 240 VAC, 50 ... 60 Hz; 20-30 VDC Transmitter "K3": PS2 power Transmitter "K4": 5 VDC @ 10 W, max Transmitter "K5": 5 VDC @ 10 W, max
Indicators/operating means	
Indicators	Transmitter "K3": video check LED Transmitter "K4": video check LED; front panel - power Transmitter "K5": video check LED; front panel - power
Display	
Screen diagonal	22" (55.9 cm)
Response time	15 ms
Resolution	1680 x 1050
Color depth	24 bit (16.7 M) color
Contrast	1000:1
Brightness	Standard: 300 nit
Reading angle	178° in all directions
Life span	Back lamp life: 50,000 hrs typical half life
Input devices	Transmitter "K3": VGA - HD15M/F; 2 x PS2 (keyboard & mouse); 1 x RS232 (touchscreen); 1 x RJ45 (CAT5e/6) Transmitter "K4": 29-pin DVI-D; 2 x USB Type A (keyboard, mouse/touchscreen); 1 x RS232 (touchscreen); 1 x RJ45 (CAT5e/6) Transmitter "K5": 29-pin DVI-D; 2 x USB Type A (keyboard, mouse/touchscreen); 1 x RS232 (touchscreen); fiber optic (multimode) LC connectors
Touchscreen	5-wire resistive
Serial data	
Baud rate	19.2 KBd max
Flow control	RTS, CTS, DTR, DSR
Directive conformity	
Electromagnetic compatibility	
Directive 89/336/EEC	EN55022A, EN61000-6-2, EN61000-3-2, EN61000-3-3 (main unit) EN55022, EN55024, IEC61000-4-2, IEC61000-4-3, IEC61000-4.4, IEC61000-4-5, EN61000-3-2, EN61000-3-3 (KVM transmitters)
Low voltage	
Directive 73/23/EEC	EN60950 (KVM transmitters)
Ambient conditions	
Operating temperature	-20 ... 50 °C (-4 ... 122 °F)
Storage temperature	-20 ... 60 °C (-4 ... 140 °F)
Relative humidity	0 ... 90% (noncondensing)
Mechanical specifications	
Protection degree	Nema Type 4X
Material	304 (UNS S30400) stainless steel
Housing	304 (UNS S30400) stainless steel
Surface	#4, 180 grit
Mass	approx. 52.16 kg (115 lbs) Empty housing ; Varies with configuration
Dimensions	813 mm x 724 mm x 381 mm (32.0 in x 28.5 in x 15.0 in) (sloping top) Volume: approx. 3.2 cu ft
Mounting	Wall or pedestal mount
International approvals	
UL approval	General purpose ; Class I, Division 2

Release date 2013-02-14 14:03 Date of issue 2013-02-14 t159182_eng.xml

